



CS 4500i | Black and White Multifunctional System

Powering Performance...
Company-wide



CS 4500i



Shown with optional 175 sheet DSDP, 500 x 2 sheet tray and 3,000 sheet side LCT



Shown with optional 175 sheet DSDP, 500 x 2 sheet tray and 1,000 sheet finisher



Shown with optional 175 sheet DSDP, 500 x 2 sheet tray, 3,000 sheet side LCT and 4,000 sheet finisher



Newly designed, easy-to-use large color touch screen control panel

HyPAS™

Hybrid Platform for Advanced Solutions



Basic Specifications

Configuration	Black & White Multifunctional System – Print / Scan / Copy / Optional Fax
Pages Per Minute	Letter: 45 ppm; Legal: 27 ppm; Ledger: 22 ppm; 12" x 18": 22 ppm (print only)
Warm-up Time	23 Seconds or Less (Power On)
First Page Out	Copy: 4.7 Seconds or less; Print: 5.3 Seconds or Less
Resolutions / Bit Depth	600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth
Memory / Hard Disk Drive	1 GB RAM Standard, 2 GB RAM Maximum / 160 GB HDD
Duplex	Standard Stackless Duplex Supports Statement to 12" x 18", 16 lb Bond – 140 lb Index (60 – 256gsm)
Standard Output Tray	Statement to 12" x 18"
Electrical Requirements	120V, 60Hz, 12.0A
Dimensions / Weight	26.30" W x 30.20" D x 29.41" H / 180.8 lbs
Max Monthly Duty Cycle	200,000 Pages Per Month

Paper Supply

Standard Paper Sources	Dual 500 Sheet Trays, 150 Sheet MPT; Auto Selection/Switching
Optional Paper Sources	Dual 500 Sheet Trays (PF-730) or Dual 1,500 Sheet Trays (PF-740); 3,000 Sheet Side Large Capacity Tray (PF-770)
Paper Capacity	Standard: 1,150 Sheets; Maximum: 7,150 Sheets
Paper Size	Trays 1,2 and PF-730: 5.5" x 8.5" – 12" x 18"; PF-740, PF-770: 8.5" x 11"; MPT: 5.5" x 8.5" – 12" x 18" (Multiple Sheet)
Paper Weight	Trays: 16 lb Bond – 120 lb index (60 – 220gsm); MPT: 16 lb Bond – 110 lb Cover (60 – 300gsm)
Input Materials	Bond Paper, Recycled Paper, Transparencies, Cardstock, Envelopes

Print Specifications

Standard Controller	IBM PowerPC 750CL / 600 MHz
PDLs / Emulations	PRESCRIBE, PCL6 (5c, XL), KPDL3 (PS3), XPS
Optional Emulation	UG-34 IBM ProPrinter, Diablo 630, LQ-850
Fonts	136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap
Windows OS Compatibility	Windows XP/2003/Vista/2008/7
Novell OS Compatibility	Novell NetWare 3.x/4.x/5.x/6.x
MAC OS Compatibility	Mac OS 10.x
UNIX OS Compatibility	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Interfaces	Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 2 USB Host Interfaces, 2 Expansion Slots Optional: 10/100/1000BaseTX (IB-50 for Dual NIC)
Network Print and Supported Protocols	TCP/IP, IPX/SPX, AppleTalk, NetBEUI, IPv6, IPsec, SSL, WSD Print
Drivers	KX Driver, Mini Driver, KX Driver for XPS, XPS Mini Driver, Network Fax Driver, PPD for MAC
Utilities	PRESCRIBE, PDF Direct Print, KMnet Admin, KMnet Viewer, Kyocera Command Center RX

Scan Specifications

Scan Resolution	200, 300, 400, 600 dpi
File Formats	BW: TIFF, XPS, PDF, PDF/A; Color: TIFF, JPEG, XPS, PDF, PDF/A
PDF Extension	High Compression PDF, Encrypted PDF
Scan Speeds	DP-770: Simplex: 75 ipm BW, 50 ipm Color (300 dpi); Duplex: 45 ipm BW, 34 ipm Color (300 dpi) DP-771: Simplex: 80 ipm BW, 50 ipm Color (300 dpi); Duplex: 160 ipm BW, 80 ipm Color (300 dpi)
Connectivity / Supported Protocols	10/100/1000BaseTX, TCP/IP
Scanning Functions	Scan to Folder (SMB), Scan to e-Mail, Scan to FTP, Scan to USB, WSD Scan, TWAIN Scan
Original Size	Through DP: Statement to 11" x 17"; Glass: up to 11" x 17"
Driver	TWAIN/WIA Driver

Copy Specifications

Image Mode	Text, Photo, Text/Photo, Auto, Manual, Map
Continuous Copy	1 – 999 / Auto Reset to 1
Additional Features	Positive/Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom
Job Management	1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy
Color Adjustment	One Touch, Hue, Auto Exposure, Sharpness
Magnification / Zoom	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, 25 – 400% in 1 step increments
Document Box	Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

Document Processor

Type / Capacity	Optional DP-770 or DP-771 DP-770: Reversing Automatic Document Processor / 100 Sheets DP-771: Dual Scan Document Processor / 175 Sheets
Acceptable Originals	5.5" x 8.5" – 11" x 17"
Acceptable Weights (Simplex / Duplex)	(DP-770) Simplex: 13 lb Bond – 90 lb Index (45 – 160gsm); Duplex 13 – 32 lb Bond (50 – 120gsm) (DP-771) Simplex: 13 lb Bond – 120 lb Index (35 – 220gsm); Duplex: 16 lb Bond – 120 lb Index (50 – 220gsm)

Fax Specifications

Compatibility / Data Compression	G3 Fax / MMR, MR, MH, JBIG
Transmission Speed / Modem Speed	Approximately 3 seconds per page / 33.6 Kbps
Fax Memory	Standard: 12 MB; Maximum: 120 MB
Driver	KM Network Fax Driver
Fax Functions	Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting, Fax Box, Dual Fax

Optional 1,000 Sheet Finisher

Stack / Staple Capacity	Main Tray: 1,000 Sheets / 50 sheets (up to 24 lb Bond (90gsm))
Paper Size	5.5" x 8.5" – 12" x 18"
Paper Weight	13 lb Bond – 110 lb Cover (45 – 300gsm)
Edge Staple Position	3 Positions: Top Left, Bottom Left, Center Bind
Optional Punch	PH-7 2 and 3 Hole Punch Unit, Supports 8.5" x 11" – 12" x 18"

Optional 4,000 Sheet Finisher

Stack / Staple Capacity	Main Tray: 4,000 Sheets; Sub Tray (B): 200 Sheets; Sub Tray (C): 100 Sheets / 65 sheets (up to 24 lb Bond (90gsm))
Paper Size	5.5" x 8.5" – 12" x 18"
Paper Weight	13 lb Bond – 140 lb Index (45 – 300gsm)
Edge Staple Position	3 Positions: Top Left, Bottom Left, Center Bind
Optional Multi-bin Mailbox	MT-730 Includes 7 Trays; Supports 16 lb Bond – 90 lb Index (60 – 163gsm) Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"
Optional Punch	PH-7 2 and 3 Hole Punch Unit, Supports 8.5" x 11" – 12" x 18"
Optional Booklet Folder / Tri-fold Unit	BF-730 Booklet Folder Supports 8.5" x 11", 8.5" x 14", 11" x 17"; 16 lb Bond – 24 lb Bond (60 – 90gsm) 16 sheets; 25 lb Bond – 28 lb Bond (91 – 105gsm) 13 sheets; Fold booklet – no staple: 16 lb Bond – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets; 32 lb Bond – 110 lb Cover (121 – 256gsm) 1 sheet; Trifold: 16 lb Bond – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets

Additional Options

Data Security Kit Provides Security Overwrite and Encryption for Print, Copy, and Scan, Optional System Memory, Optional Fax Memory, Original Hardcopy Holder (Document Tray), Card Authentication Kit

Specifications and design are subject to change without notice.

For the latest on connectivity visit www.copystar.com

All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA

©2011 Kyocera Mita America, Inc.

IC#

